Landscaping Standards and Guidelines: See sections 18.29.510-595

<u>Street Facing Yard-Intent</u>-The intent of the landscaping requirements for street-facing yards is to create a consistent landscaped area observed from the pedestrian sidewalk along all front and side streets; and to improve the aesthetics of buildings and streetscapes through the combined use of trees (as appropriate) and shrubs in street-facing yards.

- -One Tree Equivalent (TE) is equal to a 2.5 inch caliper deciduous tree; or a six-foot tall coniferous tree.
- -One Shrub Equivalent (SE) is equal to one large shrub (5 gal. container), two medium shrubs (2 gal. container); or four small shrubs (1 gal. container).

		I	D 11 C 11
	Street Facing Yards-landscaping on front and corner	Applies	Describe Compliance
	yards.	Y/N	
c1	Standard: At least 50 percent of all areas of front		
	yards that are not occupied by driveways,		
	sidewalks, or patios shall be landscaped with living		
	materials.		
c2	Standard: Except as provided in subsection c3.,		
	below, ornamental, or mid-sized trees shall be		
	installed in street-facing yards as follows:		
	Lots with 25-41ft of lot frontage1 TE		
	Lots with 41 ft of lot frontage or more2 TE		
c3	Standard: The tree-planting requirements of		
	subsection c)2., above, do not apply where the		
	applicant demonstrates that utility easements		
	(including but not limited to overhead power lines),		
	poor growing conditions due to building orientation		
	or shade, or lack of space (due to building or porch		
	disposition) would create a harmful condition or		
	prevent healthy tree growth.		
c4	Standard: A minimum of one SE of plant material		
	shall be installed for each 10 feet of primary street,		
	side street, and common court frontage of the lot		
	(as each may be present) between the building and		
	the frontage.		
d1	Guideline: Irrigated turf grass should not be planted		
	in yards (front and side) that are narrower than 4		
	feet. Layering of flowering bushes and perennials		
	should be planted instead. Rock mulch, wood		
	mulch, and ground covers are also suggested.		
d2	Guideline: A combination of ornamental trees, large		
	shrubs, and small shrubs are recommended for		
	street-facing yards (front and side) where there is		
	sufficient space and appropriate conditions for their		
	healthy growth.		
d3	Guideline: Where tree-planting is not applicable		
	pursuant to subsection c3., layered shrub		
	landscaping, including flowering shrubs, should be		
	installed near the buildings along street-facing		
	elevations;		
	however, the center third of the buildings'		
	facades should be kept clear from the shrubs.		

Landscaping Standards and Guidelines: See sections 18.29.510-595

Alleys & Shared Driveways-See Sections 18.29.560(4)

<u>Intent</u>- The intent of this subsection is to provide guidelines for alleys and shared driveways in order to improve their character and function.

	Alleys & Shared Driveways-landscaping guidelines	Applies Y/N	Describe Compliance
b1	Guideline: Landscape islands should be provided between head-in parking stalls.		
b2	Guideline: Narrow detached sidewalks (3 ft. in width) should be provided along the parking areas, and low shrubs should be installed behind car stops.		
b3	Guideline: To the extent practical, a diverse and layered landscape should be installed along alleys, including shade trees, small ornamental trees, upright shrubs, and low ground covers. However, plant selections and installation locations should prevent: A. Encroachments into the alleys that will interfere with their use; and B. Conflicts between trees and overhead or underground utilities.		
	Alleys & Shared Driveways-pavement and edges guidelines	Applies Y/N	Describe Compliance
c1	Guideline: Unnecessary pavement and hardscape on portions of the lot directly adjacent to the alley or shared driveways along the rear of several properties should be avoided.		
c2	Guideline: Pavement should be used only for the width of the garage door and gaps in pavement should be provided for planting when feasible.		
c3	Guideline: Use of straight concrete edge in lieu of regular curbs is encouraged, for it makes it easier to create landscape islands.		
c4	Guideline: The use of slotted curbs and standards is encouraged to facilitate water runoff.		